

## PREMIER PARACHUTE OPEN LIFTBAGS

Open End Parachute design with a single point attachment to the load bearing strap arrangement for safe subsea lifting.



| Model Name | Part Number | Capacity  | Overall Height(M) | Overall Diameter (M) |
|------------|-------------|-----------|-------------------|----------------------|
| M25        | 710144      | 25kg      | 0.75              | 0.40                 |
| M1         | 710140      | 50kg      | 0.85              | 0.50                 |
| M2         | 710143      | 100kg     | 1.13              | 0.50                 |
| M5         | 710168      | 250kg     | 1.92              | 0.80                 |
| M10        | 710139      | 500kg     | 2.12              | 1.00                 |
| PR1        | 710148      | 1 tonne   | 2.38              | 1.30                 |
| PR1V       | 710178      | 1.5 tonne | 2.86              | 1.30                 |
| PR2        | 710176      | 2 tonne   | 3.02              | 1.40                 |
| PR3        | 710181      | 3 tonne   | 3.95              | 1.50                 |
| PR4        | 711534      | 4 tonne   | 4.00              | 1.75                 |
| PR5        | 710182      | 5 tonne   | 4.25              | 2.20                 |
| PR6        | 711535      | 6 tonne   | 4.25              | 2.43                 |
| PR10       | 710150      | 10 tonne  | 4.85              | 2.76                 |
| PR15       | 710156      | 15 tonne  | 5.10              | 3.35                 |
| PR20       | 710152      | 20 tonne  | 5.60              | 3.67                 |
| PR25       | 711537      | 25 tonne  | 6.20              | 3.80                 |
| PR30       | 711538      | 30 tonne  | 6.10              | 4.00                 |
| PR35       | 710164      | 35 tonne  | 6.46              | 4.16                 |
| PR50       | 711317      | 50 tonne  | 7.50              | 5.00                 |

### Application:

- Safe and controlled subsea lifting operations
- Ideal for use where a single-point attachment is required

### Key Features:

- Open-end parachute design allows for rapid, controlled ascent and release of buoyancy in underwater operations.
- Simplified rigging and ensures secure connection to the load-bearing strap configuration.
- Safety inverter line automatically triggers deflation in the event of a dropped load, preventing uncontrolled ascent.
- Supplied fully assembled with a user manual and service record book for immediate use.